

PS60/500 FT15 SD

Professional two-stage V-belt driven  
compressor suitable for intensive use.

A two-stage belt driven compressor with star-delta starter designed for intensive use by professionals, it is equipped with a 15 hp pumping unit with highly efficient operation cast iron cylinders with large manifolds for better cooling and robust metal belt covers protecting moving parts. The 500-litre tank for a large air reserve with four sturdy support feet with vibration dampers make it stable in use.



TECHNICAL DATA

|                                 |        |               |
|---------------------------------|--------|---------------|
| Product code                    |        | SNTNA05PWS074 |
| Lubrication                     |        | Lubricated    |
| Compressor pump                 |        | PS60          |
| Air receiver (l)                |        | 500           |
| Power                           | Hp     | 15            |
|                                 | kW     | 11            |
| Max. pressure                   | bar    | 11            |
|                                 | p.s.i. | 160           |
| Nr. of cylinders                |        | 4V            |
| Air displacement                | l/min. | 1745          |
|                                 | c.f.m. | 61,5          |
| R.P.M.                          |        | 1200          |
| Voltage / Frequency (Volt / Hz) |        | 400/50        |
| Type motor                      |        | Electric      |
| Gross weight                    | kg     | 350           |
|                                 | lb     | 771,6         |
| Packaging dimensions LxWxH (mm) |        | 2270x860x1660 |
| EAN code                        |        | 8016738759631 |