DARWIN-E 4.0-13

# Screw compressor with belt transmission, compact and silent.

Three-phase belt-transmission lubricated screw compressor with LOGIN electronic controller and star/delta starterer. Soundproof cab in hot-dip galvanised sheet metal for maximum silence




## TECHNICAL DATA

| | | |
|---|---|---|
| Product code | | V51EW92PWSA87 |
| Lubrication | | Lubricated |
| Air-end | | FS14 |
| Air receiver (l) | | - |
| Power | | 4 |
| Air outflow | l/min. | 330 |
| | m3/min. | 0.33 |
| | c.f.m. | 12 |
| Max. pressure | bar | 13 |
| | p.s.i. | 189 |
| Nr. of stages | | 1 |
| Sound level (dB(A)) | | 60 |
| Voltage / Frequency (Volt / Hz) | | 400/50 |
| Connection (G) | | 1/2" |
| Controller | | LOGIN MINI |
| Type motor | | Electric |
| Energy efficiency | | IE3 |
| Gross weight (kg) | | 110 |
| Net weight (kg) | | 98 |
| Packaging dimensions LxWxH (mm) | | 720x670x970 |
| Net Dimensions LxWxH (mm) | | 600x550x780 |

*Sound pressure level measurement carried out at a distance of 7 metres.