NOBEL-E 15-10 PM

# Screw compressor with direct drive transmission with permanent magnet motor.

Lubricated screw compressor with coaxial transmission and inverter speed control.
Modern and versatile LOGIN electronic controller. Compact and silent

## TECHNICAL DATA

| | | |
|---|---|---|
| Product code | | V60HE97PWSA87 |
| Lubrication | | Lubricated |
| Air-end | | FS50 |
| Air receiver (l) | | - |
| Power | | 15 |
| Air outflow | l/min. | 340 / 2230 |
| | m3/min. | 0.34 / 2.23 |
| | c.f.m. | 12 / 79 |
| Max. pressure | bar | 10 |
| | p.s.i. | 145 |
| Nr. of stages | | 1 |
| Sound level (dB(A)) | | 62 |
| Voltage / Frequency (Volt / Hz) | | 400/50 |
| Connection (G) | | 3/4" |
| Controller | | LOGIN |
| Type motor | | Electric |
| Energy efficiency | | IE5 |
| Gross weight (kg) | | 235 |
| Net weight (kg) | | 215 |
| Packaging dimensions LxWxH (mm) | | 1200x810x1220 |
| Net Dimensions LxWxH (mm) | | 1020x690x960 |

*Sound pressure level measurement carried out at a distance of 7 metres.