

NOBEL 15-13-500 DF

## Screw compressor with direct drive transmission, complete with tank and dryer.

Lubricated screw compressor with coaxial transmission. LOGIN electronic controller. Compact and silent, with integrated dryer complete with prefilter and microfilter and mounted on 500-litre tank



### TECHNICAL DATA

|                                 |               |      |
|---------------------------------|---------------|------|
| Product code                    | V83CL92PWSY80 |      |
| Lubrication                     | Lubricated    |      |
| Air-end                         | FS50          |      |
| Air receiver (l)                | 500           |      |
| Power                           | 15            |      |
| Air outflow                     | l/min.        | 1550 |
|                                 | m3/min.       | 1,55 |
|                                 | c.f.m.        | 55   |
| Max. pressure                   | bar           | 13   |
|                                 | p.s.i.        | 189  |
| Nr. of stages                   | 1             |      |
| Sound level (dB(A))             | 67            |      |
| Voltage / Frequency (Volt / Hz) | 400/50        |      |
| Connection (G)                  | 3/4"          |      |
| Controller                      | LOGIN         |      |
| Type motor                      | Electric      |      |
| Energy efficiency               | IE3           |      |
| Gross weight (kg)               | 532           |      |
| Net weight (kg)                 | 491           |      |
| Packaging dimensions LxWxH (mm) | 2070x800x1850 |      |
| Net Dimensions LxWxH (mm)       | 2000x750x1670 |      |

\*Sound pressure level measurement carried out at a distance of 7 metres.