

NOBEL-E 5.5-10-270 PM

Screw compressor with direct drive transmission and permanent magnet motor with inverter, complete with tank.

Lubricated screw compressor with coaxial transmission and inverter control. LOGIN electronic controller. Compact and quiet, mounted on 270-litre tank



TECHNICAL DATA

|                                 |               |           |
|---------------------------------|---------------|-----------|
| Product code                    | V91GT97PWSA80 |           |
| Lubrication                     | Lubricated    |           |
| Air-end                         | FS26          |           |
| Air receiver (l)                | 270           |           |
| Power                           | 5,5           |           |
| Air outflow                     | l/min.        | 350-710   |
|                                 | m3/min.       | 0.35-0.82 |
|                                 | c.f.m.        | 12-29     |
| Max. pressure                   | bar           | 10        |
|                                 | p.s.i.        | 145       |
| Nr. of stages                   | 1             |           |
| Sound level (dB(A))             | 60            |           |
| Voltage / Frequency (Volt / Hz) | 400/50        |           |
| Connection (G)                  | 3/4"          |           |
| Controller                      | LOGIN         |           |
| Type motor                      | Electric      |           |
| Energy efficiency               | IE5           |           |
| Gross weight (kg)               | 275           |           |
| Net weight (kg)                 | 240           |           |
| Packaging dimensions LxWxH (mm) | 1720x750x1700 |           |
| Net Dimensions LxWxH (mm)       | 1510x690x1480 |           |

\*Sound pressure level measurement carried out at a distance of 7 metres.