

NOBEL-E 15-08-270 PM-DF (G-TEC)

Screw compressor with direct drive transmission, permanent magnet motor, complete with tank, dryer and filters.

Lubricated screw compressor with coaxial transmission and inverter control. LOGIN electronic controller. With dryer complete with installed filter package and mounted on 500-litre tank



TECHNICAL DATA

|                                 |               |           |
|---------------------------------|---------------|-----------|
| Product code                    | V91HD97PWGB80 |           |
| Lubrication                     | Lubricated    |           |
| Air-end                         | FS50          |           |
| Air receiver (l)                | 270           |           |
| Power                           | 15            |           |
| Air outflow                     | l/min.        | 400-2600  |
|                                 | m3/min.       | 0.40-2.60 |
|                                 | c.f.m.        | 14-92     |
| Max. pressure                   | bar           | 8         |
|                                 | p.s.i.        | 116       |
| Nr. of stages                   | 1             |           |
| Sound level (dB(A))             | 62            |           |
| Voltage / Frequency (Volt / Hz) | 400/50        |           |
| Connection (G)                  | 1"            |           |
| Controller                      | LOGIN         |           |
| Type motor                      | Electric      |           |
| Energy efficiency               | IE5           |           |
| Gross weight (kg)               | 334           |           |
| Net weight (kg)                 | 314           |           |
| Packaging dimensions LxWxH (mm) | 1720x750x1700 |           |
| Net Dimensions LxWxH (mm)       | 1950x690x1580 |           |

\*Sound pressure level measurement carried out at a distance of 7 metres.